



Sigma Lubricants



2T

2-Stroke Engine Oil

API TC JASO FB

Sigma 2T is one of the best oils available for use in high power and high speed imported two stroke scooters, motorcycles, autorickshws and Speed boads. When used at recommended ratio with gasoline on a well tuned engine, it gives the driver a smoother ride with high power as well as meeting the environmental regulations of the country.



TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS
ASTM Color	ASTM D 1500	Red
Specific Gravity at 15 deg	ASTM D 1298	0.8638
Viscosity at 40 deg	ASTM D 445	64.59
Viscosity at 100 deg	ASTM D 445	9.33
Viscosity Index	ASTM D 2270	123
Pour Point	ASTM D 97	-18
Flash Point	ASTM D 92	158
TBN	ASTM D 5984	-

Specifications:
Sigma 2T Meets requirements of
API TC JASO FB

Data Sheet

Furnishing the information contained herein does not constitute a representation by Sigma Oil Industries Limited that any product of process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Sigma Oil Industrues Limited or any third party. Sigma Oil Industries Limited assumes no liability for any infringement which might arise out of the use of the product. The information and suggestions to use and application presented herein represent the best information available to us and are belived to be reliable. They should not however be considered as controlling suggestions and users urged to conduct confirmatory test to determine final suitability for their specific end usage. Sigma Oil Industries Limited warranties only that it's products meet the specification which is set for them and specially **DISCLAIMS ALL OTHER WARRANTIES** relating to the products and the application thereof **EXPRESS or IMPLIED** including but not limited to warranties of **MERCHANTABILITY and FITNESS**.